



LAVALIER DYNAMIC

SPECIAL PURPOSE DYNAMIC

	D-109	D-110	D-58E	D-503	D-507
TYPE	DYNAMIC LAVALIER	DYNAMIC LAVALIER	DIFFERENTIAL	DYNAMIC	DIFFERENTIAL
DIRECTIONAL CHARACTERISTICS					
FREQUENCY RESPONSE Hz	50-15,000	50-15,000	70-12,000	50-15,000	50-15,000
UNIFORMITY OF RESPONSE**	±5 dB	±5 dB	±3 dB	±3.5 dB	±3.5 dB
SENSITIVITY†	-56 dB	-56 dB	-58 dB	-52 dB	-53 dB
IMPEDANCE	200	200	60 or 200 (specify)	200	200
FRONT-TO-BACK RATIO (1000 Hz)			25 dB	15 dB	18 dB
DIMENSIONS IN INCHES	2 3/4 x 3/8	3 3/4 x 2 3/32	1 5/8 x 1 1/8	W/shaft 17 3/5 x 2 3/8	W/shaft 17 3/5 x 2 3/8
WEIGHT	1.5 oz.	2.75 oz.	1.1 oz.	15.5 oz.	15.5 oz.
CONNECTIONS	1 = Shield 2 = Red (in phase) 3 = White Non-detachable cable	1 = Shield 2 = Red (in phase) 3 = White Non-detachable cable	1 = Shield 2 + 3 = Moving Coil Canon XLR-3	1 = Shield 2 = Red (in phase) 3 = White Non-detachable cable	1 = Shield 2 = Red (in phase) 3 = White Non-detachable cable
ACCESSORIES INCLUDED	Neck cord 30' cable Case	Neck cord w/ tie clip 30' cable Case	Built-in connector Case	13 1/2" flexible gooseneck with cable	13 1/2" flexible gooseneck with cable
PROFESSIONAL USER NET	\$49.	\$80.	\$43.	\$55.	\$55.
OPTIONAL ACCESSORIES			W-3 Windscreen MSH-58E 8" flexible gooseneck MSH-58E-2 20" flexible gooseneck MK Series Cables Standard and anti-shock stands	Standard and anti-shock stands	Standard and anti-shock stands