

International **IR** Rectifier

11DQ05

11DQ06

SCHOTTKY RECTIFIER

1.1 Amp

Major Ratings and Characteristics

Characteristics	11DQ..	Units
$I_{F(AV)}$ Rectangular waveform	1.1	A
V_{RRM}	50/60	V
I_{FSM} @ $t_p = 5 \mu s$ sine	150	A
V_F @ $1 \text{ Apk}, T_J = 25^\circ\text{C}$	0.58	V
T_J range	-40 to 125	°C


Description/Features

The 11DQ.. axial leaded Schottky rectifier has been optimized for very low forward voltage drop, with moderate leakage. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

Low profile, axial leaded out-

line

- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Very low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability



Voltage Ratings

Part number	11DQ05	11DQ06
V_R Max. DC Reverse Voltage (V)	50	60
V_{RWM} Max. Working Peak Reverse Voltage (V)		

Absolute Maximum Ratings

Parameters	11DQ..	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 4	1.1	A	50% duty cycle @ $T_A = 40^\circ\text{C}$, rectangular waveform
I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 6	150	A	5μs Sine or 3μs Rect. pulse
	25		10ms Sine or 6ms Rect. pulse Following any rated load condition and with rated V_{RWM} applied

Electrical Specifications

Parameters	11DQ..	Units	Conditions		
V_{FM} Max. Forward Voltage Drop * See Fig. 1 (1)	0.58	V	@ 1A	$T_J = 25^\circ\text{C}$	
	0.76	V	@ 2A		
	0.53	V	@ 1A	$T_J = 125^\circ\text{C}$	
	0.64	V	@ 2A		
I_{RM} Max. Reverse Leakage Current * See Fig. 2 (1)	1.0	mA	$T_J = 25^\circ\text{C}$	$V_R = \text{rated } V_R$	
	11	mA	$T_J = 125^\circ\text{C}$		
C_T Typical Junction Capacitance	55	pF	$V_R = 5V_{DC}$; (test signal range 100Khz to 1Mhz) 25°C		
L_S Typical Series Inductance	8.0	nH	Measured lead to lead 5mm from package body		

(1) Pulse Width < 300μs, Duty Cycle <2%

Thermal-Mechanical Specifications

Parameters	11DQ..	Units	Conditions
T_J Max. Junction Temperature Range	-40to125	°C	
T_{stg} Max. Storage Temperature Range	-40to125	°C	
R_{thJA} Max. Thermal Resistance Junction to Ambient	130	°C/W	DC operation Without cooling fin
R_{thJA} Typical Thermal Resistance Junction to Ambient with PC Board Mounted	81	°C/W	PC board mounted [$L=8\text{mm}(0.315\text{in.})$] Solder land area $100\text{mm}^2(0.155\text{in}^2)$
wt Approximate Weight	0.33(0.012)	g(oz.)	
Case Style	DO-204AL(DO-41)		




Fig. 1-Maximum Forward Voltage Drop Characteristics




Fig. 2-Typical Values of Reverse Current
 Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance
 Vs. Reverse Voltage




Fig.4-Maximum Ambient Temperature Vs. Average Forward Current, Printed Circuit Board Mounted




Fig.5-Forward Power Loss Characteristics




Fig.6-Maximum Non-Repetitive Surge Current