


New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
 SPRINGFIELD, NEW JERSEY 07081
 U.S.A.

TELEPHONE: (973) 376-2922
 (212) 227-6005
 FAX: (973) 376-8960

1N3491 thru 1N3495 (SILICON)

V_R — to 1000 V
 $I_O = 25$ A



Medium-current silicon rectifiers — compact, highly efficient silicon rectifiers for medium-current applications.

MAXIMUM RATINGS

Rating	Symbol	1N3491	1N3492	1N3493	1N3494	1N3495	MR327	MR328	MR330	MR331	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	$V_{RM(rep)}$ $V_{RM(wkg)}$ V_R	50	100	200	300	400	500	600	800	1000	Volts
Non-Repetitive Peak Reverse Voltage (halfwave, single phase, 60 cycle peak)	$V_{RM(non-rep)}$	100	200	300	400	500	600	720	1000	1200	Volts
RMS Reverse Voltage	V_r	35	70	140	210	280	350	420	560	700	Volts
Average Rectified Forward Current (single phase, resistive load, 60 Hz, see Figure 3) $T_C = 130^\circ C$	I_O	25									Amp
Non-Repetitive Peak Surge Current (surge applied at rated load conditions, see Figure 5)	$I_{FM(surge)}$	300 (for 1/2 cycle)									Amp
I^2t Rating (non-repetitive, for t greater than 1 ms and less than 6.3 ms)	I^2t	375									$A^2(rms)^2 sec$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-65 to +175									$^\circ C$

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	θ_{JC}	1.2	$^\circ C/watt$


MECHANICAL CHARACTERISTICS

CASE: Welded

FINISH: All external surfaces corrosion-resistant and the terminal lead is readily solderable.

POLARITY: CATHODE TO CASE (reverse polarity units are available upon request and are designated by an "R" suffix)

MOUNTING POSITIONS: Any.



Quality Semi-Conductors