

Table 1: Capacitance Data

TEST CONDITION (f = 1 MHz, Ta = 25°C)

Unit : pF

No.	C _{1V}	C _{3V}	C _{5V}	C _{8V}
1	438.0 ~ 448.9	140.00 ~ 143.51	55.00 ~ 56.37	20.00 ~ 20.50
2	446.7 ~ 457.9	142.81 ~ 146.38	56.09 ~ 57.49	20.40 ~ 20.91
3	455.7 ~ 467.0	145.66 ~ 149.31	57.21 ~ 58.64	20.81 ~ 21.33
4	464.8 ~ 476.3	148.57 ~ 152.29	58.36 ~ 59.81	21.23 ~ 21.76
5	474.1 ~ 485.9	151.55 ~ 155.34	59.53 ~ 61.01	21.66 ~ 22.19
6	483.5 ~ 495.6	154.58 ~ 158.45	60.71 ~ 62.23	22.09 ~ 22.63
7	493.2 ~ 505.5	157.67 ~ 161.6	61.93 ~ 63.47	22.53 ~ 23.08
8	503.1 ~ 515.6	160.8 ~ 164.8	63.17 ~ 64.75	22.98 ~ 23.54
9	513.2 ~ 526.0	164.0 ~ 168.1	64.43 ~ 66.04	23.44 ~ 24.01
10	523.4 ~ 536.5	167.3 ~ 171.5	65.72 ~ 67.36	23.91 ~ 24.50
11		170.7 ~ 174.9	67.04 ~ 68.71	24.38 ~ 24.99
12		174.1 ~ 178.4	68.37 ~ 70.08	24.87 ~ 25.49
13		177.6 ~ 182.0	69.74 ~ 71.48	25.37 ~ 26.00
14		181.2 ~ 185.6	71.14 ~ 72.92	25.88 ~ 26.52
15		184.8 ~ 189.3	72.56 ~ 74.37	26.40 ~ 27.05
16		188.5 ~ 193.1	74.01 ~ 75.85	26.93 ~ 27.59
17		192.3 ~ 197.0	75.49 ~ 77.37	27.47 ~ 28.15
18		196.2 ~ 201.0	76.99 ~ 78.91	28.01 ~ 28.71
19		200.0 ~ 205.0	78.53 ~ 80.49	28.57 ~ 29.28
20		204.0 ~ 209.1	80.09 ~ 82.10	29.14 ~ 29.86
21		208.1 ~ 213.3	81.70 ~ 83.74	
22		212.3 ~ 217.6	83.34 ~ 85.42	
23		216.6 ~ 221.9	85.00 ~ 87.12	
24		220.9 ~ 226.3	86.70 ~ 88.87	
25		225.3 ~ 230.8	88.43 ~ 90.64	
26		229.8 ~ 235.4	90.20 ~ 92.46	
27		234.4 ~ 240.1	92.00 ~ 94.30	
28		239.1 ~ 245.0	93.84 ~ 96.18	
29		243.8 ~ 249.9	95.72 ~ 98.11	
30			97.63 ~ 100.07	
31			99.59 ~ 102.08	
32			101.58 ~ 104.12	

- (1) This table is not selection guide, which means only to show the data.
(2) The number on the vinyl package (on the label in the vinyl package) is to show the capacitance data at each voltage in a matched group.

EXAMPLE: 4 - 3 - 2 - 1
(C_{1V}) (C_{3V}) (C_{5V}) (C_{8V})

- (3) The absolute capacitance value is in $\pm 0.5\%$.
(4) C_{8V} Classification

A : Address No.1~7
B : Address No.8~14
C : Address No.14~20

