



UNI-AND BIDIRECTIONAL TRANSIENT VOLTAGE SUPPRESSORS

- HIGH SURGE CAPABILITY :
400 W / 1 ms EXPO
- VERY FAST CLAMPING TIME :
1 ps FOR UNIDIRECTIONAL TYPES
5 ns FOR BIDIRECTIONAL TYPES
- LARGE VOLTAGE RANGE :
5.8 V → 376 V
- ORDER CODE :
TYPE NUMBER FOR UNIDIRECTIONAL
TYPES, TYPE NUMBER + SUFFIX B FOR
BIDIRECTIONAL TYPES



DESCRIPTION

Transient voltage suppressor diodes especially useful in protecting integrated circuits, MOS, hybrids and other voltage-sensitive semiconductors and components.


ABSOLUTE MAXIMUM RATINGS (limiting values)

Symbol	Parameter		Value	Unit
P_p	Peak Pulse Power for 1 ms Exponential Pulse	T_j Initial = 25 °C See note 1	400	W
P	Power Dissipation on Infinite Heatsink	$T_{amb} = 50$ °C	1.7	W
I_{FSM}	Non Repetitive Surge Peak Forward Current for Unidirectional Types	T_j Initial = 25 °C $t = 10$ ms	50	A
T_{stg} T_j	Storage and Operating Junction Temperature Range		- 55 to 150 150	°C °C
T_L	Maximum Lead Temperature for Soldering During 10 s at 4 mm from Case		230	°C

THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
$R_{th(j-l)}$	Junction-leads on Infinite Heatsink for $L_{lead} = 10$ mm	60	°C/W

Note : 1. For surges upper than the maximum values, the diode will present a short-circuit anode-cathode.



ELECTRICAL CHARACTERISTICS (T_j = 25 °C)

Symbol	Parameter	Value	
V _{RM}	Stand-off Voltage	See tables	
V _(BR)	Breakdown Voltage		
V _(CL)	Clamping Voltage		
I _{pp}	Peak Pulse Current		
α _T	Temperature Coefficient of V _(BR)		
C	Capacitance		
t _{clamping}	Clamping Time (0 volt to V _(BR))	Unidirectional Types	1 ps max.
		Bidirectional Types	5 ns max.

Types		I _{RM} @ V _{RM} max.		V _(BR) * @ I _R			V _(CL) @ I _{pp} max.		V _(CL) @ I _{pp} max.		α _T max.	C** typ. V _R =0 f=1MHz	
Unidirectional	Bidirectional	(μA)	(V)	min.	nom.	max.	(mA)	(V)	(A)	(V)	(A)	(10 ⁻⁴ /°C)	(pF)
							1ms expo		8-20μs expo				
P BZW04P5V8	P BZW04P5V8B	1000	5.8	6.45	6.8	7.48	10	10.5	38	13.4	17.4	5.7	3500
BZW04-5V8	BZW04-5V8B	1000	5.8	6.45	6.8	7.14	10	10.5	38	13.4	17.4	5.7	3500
BZW04P6V4	P BZW04P6V4B	500	6.4	7.13	7.5	8.25	10	11.3	35.4	14.5	16.0	6.1	3100
BZW04-6V4	BZW04-6V4B	500	6.4	7.13	7.5	7.88	10	11.3	35.4	14.5	16.0	6.1	3100
BZW04P7V0	P BZW04P7V0B	200	7.02	7.79	8.2	9.02	10	12.1	33	15.5	14.8	6.5	2700
BZW04-7V0	BZW04-7V0B	200	7.02	7.79	8.2	8.61	10	12.1	33	15.5	14.8	6.5	2700
BZW04P7V8	BZW04P7V8B	50	7.78	8.65	9.1	10.0	1	13.4	30	17.1	13.4	6.8	2300
BZW04-7V8	BZW04-7V8B	50	7.78	8.65	9.1	9.55	1	13.4	30	17.1	13.4	6.8	2300
BZW04P8V5	BZW04P8V5B	10	8.55	9.50	10	11.0	1	14.5	27.6	18.6	25.8	7.3	2000
BZW04-8V5	BZW04-8V5B	10	8.55	9.50	10	10.50	1	14.5	27.6	18.6	25.8	7.3	2000
P BZW04P9V4	P BZW04P9V4B	5	9.4	10.5	11	12.1	1	15.6	25.7	20.3	23.6	7.5	1750
BZW04-9V4	BZW04-9V4B	5	9.4	10.5	11	11.6	1	15.6	25.7	20.3	23.6	7.5	1750
BZW04P10	BZW04P10B	5	10.2	11.4	12	13.2	1	16.7	24	21.7	22.1	7.8	1550
BZW04-10	BZW04-10B	5	10.2	11.4	12	12.6	1	16.7	24	21.7	22.1	7.8	1550
P BZW04P11	P BZW04P11B	5	11.1	12.4	13	14.3	1	18.2	22	23.6	20.3	8.1	1450
BZW04-11	BZW04-11B	5	11.1	12.4	13	13.7	1	18.2	22	23.6	20.3	8.1	1450
P BZW04P13	P BZW04P13B	5	12.8	14.3	15	16.5	1	21.2	19	27.2	17.6	8.4	1200
BZW04-13	BZW04-13B	5	12.8	14.3	15	15.8	1	21.2	19	27.2	17.6	8.4	1200
P BZW04P14	P BZW04P14B	5	13.6	15.2	16	17.6	1	22.5	17.8	28.9	16.6	8.6	1100
BZW04-14	BZW04-14B	5	13.6	15.2	16	16.8	1	22.5	17.8	28.9	16.6	8.6	1100
P BZW04P15	P BZW04P15B	5	15.3	17.1	18	19.8	1	25.2	16	32.5	14.8	8.8	975
BZW04-15	BZW04-15B	5	15.3	17.1	18	18.9	1	25.2	16	32.5	14.8	8.8	975
BZW04P17	BZW04P17B	5	17.1	19	20	22	1	27.7	14.5	36.1	13.3	9.0	850
BZW04-17	BZW04-17B	5	17.1	19	20	21	1	27.7	14.5	36.1	13.3	9.0	850
BZW04P19	BZW04P19B	5	18.8	20.9	22	24.2	1	30.6	13	39.3	12.2	9.2	800
BZW04-19	BZW04-19B	5	18.8	20.9	22	23.1	1	30.6	13	39.3	12.2	9.2	800
BZW04P20	P BZW04P20B	5	20.5	22.8	24	26.4	1	33.2	12	42.8	11.2	9.4	725
BZW04-20	BZW04-20B	5	20.5	22.8	24	25.2	1	33.2	12	42.8	11.2	9.4	725
P BZW04P23	BZW04P23B	5	23.1	25.7	27	29.7	1	37.5	10.7	48.3	9.9	9.6	625
BZW04-23	BZW04-23B	5	23.1	25.7	27	28.4	1	37.5	10.7	48.3	9.9	9.6	625
P BZW04P26	P BZW04P26B	5	25.6	28.5	30	33	1	41.5	9.6	53.5	9.0	9.7	575
BZW04-26	BZW04-26B	5	25.6	28.5	30	31.5	1	41.5	9.6	53.5	9.0	9.7	575
BZW04P28	P BZW04P28B	5	28.2	31.4	33	36.3	1	45.7	8.8	59	81.5	9.8	510
BZW04-28	BZW04-28B	5	28.2	31.4	33	34.7	1	45.7	8.8	59	81.5	9.8	510
P BZW04P31	P BZW04P31B	5	30.8	34.2	36	39.6	1	49.9	8	64.3	74.5	9.9	480
BZW04-31	BZW04-31B	5	30.8	34.2	36	37.8	1	49.9	8	64.3	74.5	9.9	480
P BZW04P33	BZW04P33B	5	33.3	37.1	39	42.9	1	53.9	7.4	69.7	69	10.0	450

* Pulse test t_p ≤ 50 ms δ < 2 %

** Divide these values by 2 for bidirectional types.

For bidirectional types, electrical characteristics apply in both directions

P : Preferred device

Types		I _{RM} @ V _{RM} max.		V _(BR) * @ I _R			V _(CL) @ I _{PP} max.		V _(CL) @ I _{PP} max.		α _T max.	C** typ. V _R =1MHz f=1MHz		
Unidirectional	Bidirectional	(μA)	(V)	min.	nom.	max.	(mA)	(V)	(A)	(V)	(A)	(10 ⁻⁴ /°C)	(pF)	
	BZW04-33	5	33.3	37.1	39	41	1	53.9	7.4	69.7	69	10.0	450	
	BZW04P37	P	5	36.8	40.9	43	47.3	1	59.3	6.7	76.8	62.5	10.1	400
	BZW04-37		5	36.8	40.9	43	45.2	1	59.3	6.7	76.8	62.5	10.1	400
	BZW04P40		5	40.2	44.7	47	51.7	1	64.8	6.2	84	57	10.1	370
	BZW04-40		5	40.2	44.7	47	49.4	1	64.8	6.2	84	57	10.1	370
	BZW04P44		5	43.6	48.5	51	56.1	1	70.1	5.7	91	52.5	10.2	350
	BZW04-44		5	43.6	48.5	51	53.6	1	70.1	5.7	91	52.5	10.2	350
	BZW04P48		5	47.8	53.2	56	61.6	1	77	5.2	100	48	10.3	320
	BZW04-48		5	47.8	53.2	56	58.8	1	77	5.2	100	48	10.3	320
	BZW04P53		5	53	58.9	62	68.2	1	85	4.7	111	43	10.4	290
	BZW04-53		5	53	58.9	62	65.1	1	85	4.7	111	43	10.4	290
	BZW04P58		5	58.1	64.6	68	74.8	1	92	4.3	121	39.5	10.4	270
	BZW04-58		5	58.1	64.6	68	71.4	1	92	4.3	121	39.5	10.4	270
	BZW04P64		5	64.1	71.3	75	82.5	1	103	3.9	134	36	10.5	250
	BZW04-64		5	64.1	71.3	75	78.8	1	103	3.9	134	36	10.5	250
	BZW04P70	P	5	70.1	77.9	82	90.2	1	113	3.5	146	33	10.5	230
	BZW04-70		5	70.1	77.9	82	86.1	1	113	3.5	146	33	10.5	230
	BZW04P78		5	77.8	86.5	91	100	1	125	3.2	162	29.5	10.6	210
	BZW04-78		5	77.8	86.5	91	95.5	1	125	3.2	162	29.5	10.6	210
P	BZW04P85		5	85.5	95	100	110	1	137	2.9	178	27	10.6	200
	BZW04-85		5	85.5	95	100	105	1	137	2.9	178	27	10.6	200
	BZW04P94		5	94	105	110	121	1	152	2.6	195	24.5	10.7	185
	BZW04-94		5	94	105	110	116	1	152	2.6	195	24.5	10.7	185
	BZW04P102		5	102	114	120	132	1	165	2.4	212	22.5	10.7	170
	BZW04-102		5	102	114	120	126	1	165	2.4	212	22.5	10.7	170
P	BZW04P111		5	111	124	130	143	1	179	2.2	230	20.8	10.7	165
	BZW04-111		5	111	124	130	137	1	179	2.2	230	20.8	10.7	165
P	BZW04P128	P	5	128	143	150	165	1	207	2.0	265	18.1	10.8	145
	BZW04-128		5	128	143	150	158	1	207	2.0	265	18.1	10.8	145
P	BZW04P136	P	5	136	152	160	176	1	219	1.8	282	17	10.8	140
	BZW04-136		5	136	152	160	168	1	219	1.8	282	17	10.8	140
P	BZW04P145		5	145	161	170	187	1	234	1.7	301	16	10.8	135
	BZW04-145		5	145	161	170	179	1	234	1.7	301	16	10.8	135
	BZW04P154		5	154	171	180	198	1	246	1.6	317	15.1	10.8	125
	BZW04-154		5	154	171	180	189	1	246	1.6	317	15.1	10.8	125
	BZW04P171		5	171	190	200	220	1	274	1.5	353	13.6	10.8	120
	BZW04-171		5	171	190	200	210	1	274	1.5	353	13.6	10.8	120
	BZW04P188	P	5	188	209	220	242	1	301	1.4	388	12.4	10.8	110
	BZW04-188		5	188	209	220	231	1	301	1.4	388	12.4	10.8	110
P	BZW04P213		5	213	237	250	275	1	344	1.5	442	12	11	100
	BZW04-213		5	213	237	250	263	1	344	1.5	442	12	11	100
P	BZW04P239		5	239	266	280	308	1	384	1.5	494	12	11	95
	BZW04-239		5	239	266	280	294	1	384	1.5	494	12	11	95
	BZW04P256		5	256	285	300	330	1	414	1.2	529	10	11	90
	BZW04-256		5	256	285	300	315	1	414	1.2	529	10	11	90
	BZW04P273		5	273	304	320	352	1	438	1.2	564	10	11	85
	BZW04-273		5	273	304	320	336	1	438	1.2	564	10	11	85
P	BZW04P299		5	299	332	350	385	1	482	0.9	618	9	11	80
	BZW04-299		5	299	332	350	368	1	482	0.9	618	9	11	80
	BZW04P342		5	342	380	400	440	1	548	0.9	706	8	11	75
	BZW04-342		5	342	380	400	420	1	548	0.9	706	8	11	75
	BZW04P376		5	376	418	440	484	1	603	0.8	776	8	11	70
	BZW04-376		5	376	418	440	462	1	603	0.8	776	8	11	70

* Pulse test t_b < 50 ms δ < 2%.

** Divide these values by 2 for bidirectional types.

For bidirectional types, electrical characteristics apply in both directions.

P: Preferred device.




Fig.1 - Peak pulse power versus exponential pulse duration.




Fig.2 - Clamping voltage versus peak pulse current.
 exponential waveform $t = 20 \mu s$
 $t = 1 ms$ ---
 $t = 10 ms$ —

Note : The curves of the figure 2 are specified for a junction temperature of 25 °C before surge. The given results may be extrapolated for other junction temperatures by using the following formula : $\Delta V (BR) = \alpha \cdot V (BR) \cdot [T_j - 25] \cdot V (BR)$
 For intermediate voltages, extrapolate the given results.

D88BZW04P4




Fig. 3 - Allowable power dissipation versus junction temperature.




Fig. 4 - Power dissipation versus ambient temperature.




Fig. 5 - Thermal resistance versus lead length.




Fig. 6 - Transient thermal impedance junction-ambient for mounting n°2 versus pulse duration ($L = 10 \text{ mm}$).





Fig. 7 - Peak forward current versus peak forward voltage drop (typical values for unidirectional types).

D88BZW04P5




Fig.8a - Capacitance versus reverse applied voltage for unidirectional types (typical values).





Fig.8b - Capacitance versus reverse applied voltage for bidirectional types (typical values).

D88BZW04P6

PACKAGE MECHANICAL DATA

F 126 Plastic



Ref.	Millimeters		Inches		Notes
	Min.	Max.	Min.	Max.	
Ø b ₂	0.76	0.86	0.029	0.034	1 - The lead diameter Ø b ₂ is not controlled over zone L ₁ . 2 - The minimum axial length within which the device may be placed with its leads bent at right angles is 0.59" (15 mm).
Ø D	2.95	3.05	0.116	0.120	
G	6.05	6.35	0.238	0.250	
L	26	-	1.024	-	
L ₁	-	1.27	-	0.050	

Cooling method : by convection (method A)

Marking : type number ; white band indicates cathode for unidirectional types

Weight : 0.4 g